VEHICLE MANAGING METHOD

BACKGROUND OF THE INVENTION

The present invention relates to a method for collecting information on movable bodies by making use of a satellite communications system or other mobile telecommunications system (ground-based digital communications, cellular phones, DSRC, etc.).

There have been a number of car navigation systems put into practical use, which show on their screens where a vehicle is currently located, and later years have even witnessed a communications navigation system that connects cellular phones with car navigation systems.

A common means of obtaining vehicle status information is, instead of adopting a real-time system, to prepare part of historical data of a vehicle when the vehicle is inspected at a dealer and the data is transmitted to a committed automobile manufacturer or a vehicle parts manufacturer through cable telecommunications.

The existing vehicle insurance system employs a scheme of paying premiums on an annual contract basis regardless of frequency of utilization of the vehicle.

A system is available as a means of obtaining

vehicle status information, in which part of historical data of the vehicle is acquired through cable connections when the vehicle is inspected at a dealer. Because of a low frequency of collection and uncertainty about the vehicle's being driven into a specific dealer for inspection involved in this method, it is difficult for a committed vehicle manufacturer or a parts manufacturer to make a statistical analysis of the data, set up a marketing plan for each model, and give feedback information to an upstream design function. To collect and manage data for each model of vehicles manufactured by a specific manufacturer through cellular phones, which have spread at a rapid pace as an embodiment of mobile telecommunications technology, it becomes necessary to have telephone numbers of all users and it is difficult to collect information from, and send information to, multiple specific vehicles.

Furthermore, since it is currently impossible to have statistical data on utilization of vehicles, users have no choice but to conclude an annual contract with a nonlife insurance company regardless of the frequency of utilization of the vehicle, making it impossible to pay insurance premiums in proportion to utilization frequency and utilization status, and in accordance with many varied

other needs.

When a used vehicle is assessed, the assessment made
is not solid at all, being carried out by simply filling
out a check sheet and exchanging photos. It is therefore
difficult to evaluate vehicle conditions in terms of
aspects other than appearance based on data available from
vehicles of the same model, same model year, and similar
mileage.

It has not therefore been common practice at all to
collect information on current vehicle conditions
continuously on a real-time basis, or if it has ever been
so, it has been concerned only with a limited, narrow area
and the information collected in this manner could never be
useful. Continuously collecting information on vehicle
conditions is indispensable to a statistical analysis of
the vehicle and model. Without such statistics, no
diagnostic analysis can be made.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to
provide, in terms of vehicle insurance, a method for
processing vehicle insurance premium charge that allows an
insured person to pay premiums in accordance with frequency

and conditions of utilization of a vehicle by continuously
collecting information on current vehicle conditions in
details, positively, and on a real-time basis and making a
statistical analysis thereof.

It is also another of the invention to provide, by
taking the opportunity of making this proposal, a
comprehensive interactive vehicle management method that
makes it possible to provide information providing
organizations with vehicle information in areas other than
insurance and, at the same time, provide vehicle users with
various broadcasting and communications information.

According to one aspect of the present invention, a
vehicle managing method includes the steps of distributing
music and/or image through a satellite to each of vehicles
with which a contract for music distribution and/or image
distribution has been made, or distributing information in
one category, or two or more categories, selected from
among music, image, navigation, road and traffic, emergency,
and new vehicle information categories, and at the same
time, receiving periodic information on each of the
contracted vehicles therefrom via the satellite, analyzing
the received information for each vehicle, and transmitting
the analysis information to a predetermined recipient of

the analysis information.

Preferably, the periodic information may be on, for example, at least one of the followings; namely, the position, speed, direction, and condition of the vehicle. It would be particularly practical if the periodic information is driving time data and via point data representing geographical points, areas, or routes through which the vehicle moves that would be obtained by combining the different types of information noted earlier. In addition to the periodic information transmitted to the satellite from each of the contracted vehicles, it is desirable that emergency information concerning the vehicle be also transmitted. Preferably, possible recipients of the analysis information are selected from among groups of an insurance company, road maintenance company, supervisory agency, governmental organization, vehicle management company, vehicle maintenance company, and vehicle dealer. It is even more desirable that the information transmitted from vehicles at periodic intervals be stored in a storage medium at an interval shorter than the predetermined interval for the periodic information and accumulated data be transmitted in a batch at the predetermined interval.

A preferred artificial satellite system applied to

the invention is, for example, one that uses a non-geostationary satellite that is in a highly elliptic orbit, as that incorporated in European Patent Laid-open No.0880240A2. This elliptic orbit system has the minimum elevation angle over the service area is not less than 40° ,for the purposes of sharing with terrestrial services.

Typical operations of transmission and reception of information carried out in the vehicle managing method according to the invention may be as follows.

(1) Vehicle position information is found and collected by using a signal reflected off an artificial satellite after the signal has been transmitted thereto through an antenna provided in a controlled vehicle, and information on a condition of each individual vehicle is collected by transmitting vehicle control information or vehicle parts condition information from the controlled vehicle to the artificial satellite through the antenna provided in the controlled vehicle and receiving a signal reflected off the artificial satellite or by transmitting the information by way of DSRC (dedicated short range communication; the same abbreviation of DSRC is to be used hereunder) or a mobile communications device including a cellular phone and receiving the transmitted signal.

(2) Vehicle position information is found and collected by using a signal reflected off an artificial satellite after the signal has been transmitted thereto through an antenna provided in a controlled vehicle, information on the conditions of each individual vehicle is collected by transmitting vehicle sensor information to the artificial satellite through the antenna provided in the controlled vehicle and receiving a signal reflected off the artificial satellite or by transmitting the information by way of DSRC or a mobile communications device including a cellular phone and receiving the transmitted signal, and individual vehicle information is collected together with vehicle body information including a vehicle model and serial number, as well as user information unique to the controlled vehicle separately input.

(3) Vehicle position information is found and collected by using a signal reflected off an artificial satellite after the signal has been transmitted thereto through an antenna provided in a controlled vehicle, information on a condition of each individual vehicle is collected by transmitting vehicle control information and vehicle parts condition information from the controlled vehicle to the artificial satellite through the antenna

provided in the controlled vehicle and receiving a signal

reflected off the artificial satellite or by transmitting

the information by way of DSRC or a mobile communications

device including a cellular phone and receiving the

transmitted signal, and individual vehicle information is

collected by transmitting vehicle condition information

extracted from a diagnostics system mounted in the

controlled vehicle, based on a command issued by the

diagnostics system to transmit diagnostics results

information, from the controlled vehicle to the artificial

satellite and receiving a signal reflected therefrom,

together with vehicle body information including a vehicle

model and serial number, as well as user information unique

to the controlled vehicle separately input.

(4) Information on a condition of each individual

vehicle is collected by transmitting vehicle control

information or vehicle parts condition information from a

controlled vehicle to an artificial satellite through an

antenna provided in the controlled vehicle and receiving a

signal reflected off the artificial satellite.

(5) Information on a condition of each individual

vehicle is collected by transmitting vehicle sensor

information to an artificial satellite through an antenna

provided in a controlled vehicle and receiving a signal reflected off the artificial satellite, and vehicle body information including a vehicle model and serial number, as well as user information unique to the controlled vehicle separately input.

(6) Information on a condition of each individual vehicle is collected by transmitting vehicle control information and vehicle parts condition information from a controlled vehicle to an artificial satellite through an antenna provided in the controlled vehicle and receiving a signal reflected off the artificial satellite and by transmitting vehicle condition information extracted from a diagnostics system mounted in the controlled vehicle, based on a command issued by the diagnostics system to transmit diagnostics results information, from the controlled vehicle to the artificial satellite and receiving a signal reflected therefrom, together with vehicle body information including a vehicle model and serial number, as well as user information unique to the controlled vehicle separately input.

The vehicle managing method according to the invention further provides the following system. Namely, position information, speed information, vehicle condition

information (information on an engine and electrical and mechanical system), and safety and crisis management information are collected from the vehicle on a real-time basis. These pieces of data are managed overall and analyzed to identify a vehicle operation management status, readiness to ensure safety and cope with hazardous situations, traffic congestion status, and utilization of the vehicle, thereby building a mobile information overall management system that provides various kinds of services. While providing transportation companies, road maintenance agencies, vehicle manufacturers, and traffic information providers with charged data, the overall information management system has the transportation companies, road maintenance agencies, and vehicle manufacturers distribute individual information to each vehicle. It is preferable, in this system, that a contract governing information exchange be concluded between the mobile information management system and the vehicle users, and between the mobile information management system and transportation companies, road maintenance agencies, and vehicle manufacturers, thereby allowing the mobile information management system to earn the wherewithal to sustain itself from the contracts. It is further preferable, in this

system, that the mobile information management system be run with enhanced convenience for the vehicle users by letting the mobile information management system broadcast music or image, in addition to enabling interactive communications.

In addition, preferably, information obtained from vehicles may be analyzed by the mobile information management system and, if a vehicle trouble is anticipated, that information is passed onto not only the corresponding driver, but also the vehicle manufacturer or a designated dealer including a maintenance service shop so that the designated dealer may dispatch a technician who is capable of performing repair and service jobs to a location specified by the driver and who may carry with him or her service and replacement parts as necessary to perform a quick service job at the specified location. It is preferable in this system that operation characteristics of the driver be analyzed to calculate the insurance premiums.

If the invention is to be applied to insurance charging, it is an object of the invention to find and collect vehicle position information by classifying vehicle condition information into two groups, namely, the vehicle position information and other information which may, for

example, include vehicle control information, vehicle parts

condition information, vehicle body information, user

information, and vehicle maintenance and historical

information, and by using a signal reflected off the

artificial satellite after the signal has been transmitted

thereto through an antenna provided in the vehicle. The

signal reflected off the artificial satellite after it has

been transmitted thereto through the antenna has

conventionally been used to find a vehicle position for use

in navigation; however, it has never been done to collect

and analyze the obtained vehicle position information.

Moreover, if the invention is to be applied to insurance

charging, it is practical to allow a statistical analysis

to be made of both vehicle position information and other

vehicle information combined by collecting other

information in addition to vehicle position information.

The foregoing two means make it possible to accumulate

detailed and positive vehicle information about each

individual vehicle on a real-time basis, permitting

application to vehicle insurance premium charging

processing.

Furthermore, if the invention is to be applied to

insurance charging, a method is executed in which driving

time data for a predetermined period of time (which could

be one day) of a contracted vehicle is collected and

statistically analyzed and via point data representing

geographical points, areas, or routes through which the

vehicle has been driven (hereinafter referred generically

to points) is collected and analyzed, thereby permitting

payment of insurance premiums in accordance with vehicle

utilization frequency and conditions. One of the most

important points that are realized through executing the

method is that it permits deferred payment of insurance

premiums that vary in accordance with vehicle utilization

frequency and condition, instead of the conventional

advance payment on an annual contract basis. It goes

without saying that it is possible to revise existing

contracted premiums using the data collected and analyzed

as described heretofore.

The following specific methods may be applied if the

invention is to be embodied in insurance charging. That is,

in a vehicle insurance premium charging processing method

in which vehicle insurance premiums established and charged

according to a contract concluded with the vehicle user,

driving time for a predetermined period of time of a

contracted vehicle is collected and via points data

representing points through which the contracted vehicle

has been driven is collected; charging time data is

established based on the driving time and a weighting of

insurance premiums is established based on the charging

time data or via point data, or both, thereby displaying

the amount charged as insurance premiums based on the

charging time data, via point data, and insurance premium

weighting. The insurance premium weighting is a premium

rate. The via point data includes points registered as

being known, points yet to be registered because they are

unknown, and points registered as being accident-ridden,

and a low insurance premium weight is assigned to the

points registered as being known and a high insurance

premium weight is assigned to the points yet to be

registered because they are unknown and points registered

as being accident-ridden. For the purpose of the weighting

of insurance premiums, vehicle control information, vehicle

parts condition information, user information or

maintenance and historical information concerning the

vehicle and user, and other information are to be used.

Furthermore, points are calculated using the charging time

and weighted via point data and the premium rate and

insurance money are determined based on the points obtained

through calculation.

An embodiment of the invention is as follows. That is, in a charged service system in which basic information of music and image is distributed to a vehicle and fees are collected from viewers-listeners, information transmitted from the vehicle is collected at an overall information center which, in turn, analyzes the information and transmits it to vehicle management organizations, road management organizations, and insurance organizations, and information from these management centers is transmitted to vehicles, thereby improving service functions for the viewers-listeners and consequently raising the fees for the charged services.

A first embodiment of data analysis is concerned with a position, speed, and direction of a vehicle of the information provided by the vehicle. The information representing these pieces of data is collected from all vehicles on the road at predetermined intervals, which identifies a traveling speed of vehicles on each traffic, thus showing the condition of traffic congestion. When combined with information provided by the road management center, the information helps enhance accuracy of traffic congestion information. A vehicle driver, on the other

hand, can have information on congestion conditions of not only nearby places, but also a remote destination and is allowed to obtain from the road management organization detour information and traffic information on roads which are less congested. It is also possible, by analyzing information provided by the vehicles located in tunnels, bridges, or road sections under construction, to detect any unusual conditions present in these areas. By adding time-of-day factor to these information, it is possible to analyze characteristics of utilization of vehicles by users, that is, whether the vehicles are used for weekend vacationing in resorts, for day-to-day shopping, or for nighttime driving or business. This serves as useful data for vehicle dealers when they make recommendations for vehicle models as customers decide to buy new ones next time. It is also possible to analyze driving habits and characteristics of the driver, including application of sudden braking and whether he or she tends to rev up to the maximum speed. This provides useful data not only for the vehicle dealer, but also for the insurance company for making a danger prediction analysis of the driver in its effort to reduce premium rate for good drivers.

A second embodiment of data analysis uses

information provided from the vehicle, particularly the amount of fuel still available for use and mileage. Since the amount of fuel still available for use and mileage allow an analysis to be made of fuel economy of the vehicle, the vehicle management organization can use the data for evaluating the vehicle and improving performance. If such data is made available to users, it means that data for selecting vehicles is disclosed, thus enhancing convenience for the users.

A third embodiment of data analysis uses information provided from the vehicle, particularly exhaust gases (CO_2, CO, NO, NO_2, SO_2, and amounts of soot and other particles). The condition of the vehicle is identified by analyzing exhaust gases therefrom and the user is informed of whether the vehicle needs maintenance, or oil or a part needs replacement. The vehicle management organization is then provided with data that allows an analysis to be made of engine conditions and specific road conditions affecting vehicle characteristics, thus making use of data in developing new vehicles and improving existing ones.

A fourth embodiment of data analysis uses information provided from the vehicle, particularly conditions in which an air bag is activated, collision

acceleration speed, vehicle tilt (the vehicle is considered
to be rolled over if tilted to a predetermined angle or
more), and an emergency communication (button or voice)
made from the driver. Such information, as it contains
data representing an unusual condition or emergency of the
vehicle, allows the vehicle management center or road
management center to resort to emergency mobilization.

A fifth embodiment of data analysis permits
continuous collection of information of the following types,
since information furnished by the vehicle can be stored in
a storage medium by taking readings at much shorter
intervals and transmitted in a batch at predetermined
intervals. Namely, since it is possible to collect
detailed information on vehicle speed, vehicle direction,
acceleration, number of times the brake is applied, and
vehicle-to-vehicle distance (measured using a radar), the
information is useful in making an analysis in even greater
detail of the driving habits and characteristics of the
user noted earlier. The analysis of such information
permits an accurate analysis of the route the vehicle has
followed, which makes it possible to gain information on
road conditions in even greater detail.

A sixth embodiment of data analysis uses traffic

congestion analysis information as the information provided from the vehicle. Thanks to these pieces of information, the road management center can identify specific spots at which, and particular time bands during which, traffic congestion tends to occur, thereby providing vehicle users with appropriate congestion bypass prediction information before they run into the jam. The users, on the other hand, can use traffic congestion prediction information to select a route and a time band to bypass congestion, which as a result contributes to easing traffic congestion.

A seventh embodiment of data analysis is to analyze operating information of a company's fleet, figure out an optimum deployment of the fleet, and formulate an operating schedule. Managing the operating condition of a company's fleet optimizes vehicle operation and cargo loading control. It is also possible to instruct a vehicle on what to do next by making use of advantages of interactive communications. Health care and safety operation management is also possible, including instructing a driver to take a rest through driver's tiredness check.

An eighth embodiment of data analysis is concerned with driver's tiredness check. A driver may be advised to take a rest to ensure utmost safety through monitoring of

driving conditions, or the movement of eyeballs, and driver's tiredness as determined by checks on turning of the steering wheel, acceleration, and braking. A driver's tiredness check and a check for dozing off at the wheel, made based on a vehicle-to-vehicle distance determined with a radar and the number of sudden brakes applied, are analyzed to allow an accident preventive function that warns the driver before an accident actually happens to be exhibited. The interactive communication function is used to allow the center to send an emergency transmission of warning data such as a buzzer.

While the invention will be described in its preferred embodiment in vehicles, it is understood that the invention is applicable to other movable bodies including ships. Furthermore, although reception at movable bodies is mandatory, it does not exclude a case in which information is received by fixed terminals including homes.

According to the invention, it is preferable that periodic information be received once in 5 to 10 minutes (at which intervals, it is possible to determine traffic on the road based on the distance traveled by the moving object). Considering the time it takes the periodic information to be transmitted (even with a lag of 1 to 2

minutes), there is no problem involved since the

information being transmitted is appended with the time of

measurement. It is further possible to change the

frequency in the middle of operations (which requires a

command issued from a master station).

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a conceptual diagram showing an

interactive satellite communications service system

according to an embodiment of the invention;

FIG. 2 is a conceptual diagram showing a case of

providing traffic congestion information in the above

system according to the embodiment of the invention;

FIG. 3 is a diagram of a typical screen presenting

congestion information employing the embodiment of the

invention;

FIG. 4 is a diagram showing a typical record of

driver's actions employing the embodiment of the invention;

FIG. 5 is a diagram showing a typical screen

presenting part of statistical traffic information

employing the embodiment of the invention;

FIG. 6 is a characteristic diagram showing the

results of simulation of call loss probability employing

the embodiment of the invention;

FIG. 7 is a timing chart showing a transmission/reception relationship between a movable body and a ground station according to the embodiment of the invention;

FIG. 8 shows a diagram of status transition on the ground station side in FIG. 7;

FIG. 9 shows a diagram of status transition on the movable body side in FIG. 7;

FIG. 10 is a conceptual diagram showing a typical movable body overall information management system according to the embodiment of the invention;

FIG. 11 is a conceptual diagram showing a typical movable body overall information management system according to the embodiment of the invention;

FIG. 12 is a conceptual diagram showing interactive communications operations performed by the system embodying the invention;

FIG. 13 is a diagram showing interactive communications operations performed by the system embodying the invention;

FIG. 14 is a diagram illustrating basic functions offered by the transmission/reception terminal of the

system embodying the invention;

FIG. 15 is a conceptual diagram showing another system embodying the invention;

FIG. 16 is a block diagram showing the functions of an on-vehicle device;

FIG. 17 is a block diagram showing the functions of a centralized management center;

FIG. 18 is a conceptual diagram showing a satellite communications broadcasting system according to the embodiment of the present invention;

FIG. 19 is a flowchart showing a vehicle condition online managing method according to the embodiment of the present invention;

FIG. 20 is a flowchart showing a vehicle information providing service method according to the present invention of the invention; and

FIG. 21 is a block diagram showing the flow of information services and contract fees in the basic business of "music/broadcast + interactive communication."

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENYS

Hereinafter, a vehicle managing method according to an embodiment of the invention will be described with

reference to the accompanying drawings.

FIG. 1 is a schematic drawing showing the concept of an interactive satellite communications service used in the invention. This service allows interactive communications 6 to be carried out between an artificial satellite 1 and each of contracted vehicles 4 and interactive communications 5 to be carried out between a service center 2 and the artificial satellite 1 via an antenna 3. Though named a communications system, it may distribute image and music by broadcasting. The same holds true hereunder in this specification.

The service center 2 provides the following services under this system. (1) Providing traffic congestion information: A trajectory of a local vehicle is compared with statistical information and traffic of a scheduled route is predicted. A typical communications band (from a vehicle to the center) required for this service is several kbps multiplied by the number of vehicles. (2) Managing vehicle locations: This represents a control of vehicle movements to enable highly efficient management through giving delivery instructions. A typical communications band (from a vehicle to the center) required for this service is several kbps multiplied by the number of

vehicles. (3) Telemetry service: Various types of control information are collected through the vehicle and the information is provided by way of a network. A typical communications band (from a vehicle to the center) required for this service is also several kbps multiplied by the number of vehicles. (4) Charging system: This represents user control including restricted reception and e-commerce. A typical communications band (from a vehicle to the center) required for this service is, at most, several bps multiplied by the number of vehicles. (5) Audi/image communications: This represents audio and image communications carried out in accordance with MPEG, AAC, and other standard format. A typical communications band (from the center to a vehicle) required for this service is several hundred kbps multiplied by the number of programs. (6) Security service: An application of the emergency information system (Help Net), this service requires a communications band (from a vehicle to the center) of several kbps multiplied by the number of vehicles.

Referring to FIG. 2, a case of providing traffic congestion information is described as an example of uplink applications. In this case, the center 2 in FIG. 1 may, for example, be a traffic congestion information center 7.

- 26 -

The center 7 edits traffic information, distributes traffic

information, merges various types of information, and

analyzes moving vehicle information. Communications are

interactive between the center 7 and a satellite 1. To be

more specific, traffic information 8 is transmitted from

the center 7 to the satellite 1, while moving vehicle data

9 is received at the center 7 by way of the satellite 1.

The traffic information 8 is delivered to each of

contracted vehicles 4 via the satellite 1, while the moving

vehicle data 9 is derived from each of the contracted

vehicles 4. Each vehicle is an authorized member or a

probe car (with which road and traffic information is

determined). Each vehicle is, in a nutshell, supposed to

gather moving vehicle data (position, speed).

To describe this example as applied to a case in

Japan, suppose that all areas of Tokyo metropolitan trunk

roads are covered for real-time information with an average

information update interval of 5 min. Base on the average

vehicle speed of about 20 km/h in the Kanto seaside

district (taken from Metropolitan Tokyo Regional Disaster

Prevention Plan HP), the distance traveled for 5 min. is 20

x 5/60 = 1.67 km and the total length of Tokyo metropolitan

national highways and municipal highways is 2,625.0 km (as

of April 1, 1998), a total of 5,250 km to count roads up and down in both directions (2,625.0 x 2). To obtain real-time information, it would be effective if there are available 5,250/1.67 = 3,150 vehicles. An estimated number of moving vehicles at any given point in time on Tokyo metropolitan trunk roads is obtained as follows: namely, average density x total length of roads = traffic/average speed x total length of roads = [13,190 (traffic for 12 hours)/12/20] x 5,250 = 288,531 vehicles. Then, probe car ratio γ = 3,150/288,531 = 1.09% and, if probe cars are placed at predetermined intervals, it is preferable that the probe car ratio be two to three times as large as 1.09% when they are placed at random. Considering the fact that there are only part of vehicles equipped with on-board terminals running on the roads and suppose that the number of vehicles in operation in the Tokyo metropolitan area (as of the end of 1996, excluding two-wheeled vehicles and special-purpose vehicles) is 4,108,109, it is effective if the number of terminals is as follows; namely, the number of vehicles in operation x probe car ratio = 4,108,109 x 1.09/100 = 44,778.

FIG. 3 shows a typical screen representing congestion information. It shows a trajectory through

which vehicles are driven according to the speed on a traveling map. For ease of identification on a black-and-white drawing of the example figure, a solid line represents a smoothly flown traffic, a dashed line represents a crowded traffic, and a dotted line represents a congested traffic. Instead of using different types of lines, coloring may be used in actual applications. A portion marked with a reference numeral 10 in the FIG. is provided with arrows for scrolling the displayed portion on the map and an enlargement and reduction buttons. A reference numeral 11 represents a sub-screen entitled "Probe Car" and a reference numeral 12 is a legend. A still another sub-screen or an independent screen may be displayed to show a record of driver's actions as shown in FIG. 4 or statistical traffic information as shown in FIG. 5. The statistical traffic information shown in FIG. 5 may be produced as a hard copy as part of automatic generation of journals. In any event, it serves as a basis for predicting traffic along the schedule route through comparison between the statistical information and a trajectory of the local vehicle. It is preferable that the lines representing different types of data in FIG. 5 be colored for ease of identification.

The result of simulation of call loss probability will be described referring to FIG. 6. The term "call loss probability" refers to a rate of failure in successful transmission of information (the call loss probability is 3% when there are three successfully completed calls out of 100 attempted calls). The data shows that the call loss probability is 0.2 (20%) which seems to be rather high; however, retrial greatly improves the probability of putting the call through. If the call loss probability is 0.2 and there are three retrials (that is, it is attempted to transmit a signal four times in total), the total call loss probability would be 0.2 x 0.2 x 0.2 x 0.2 x 0.2 = 0.0016, or a ratio of successfully completing calls would be 0.9984.

Suppose that the center 2 is a ground station provided with 100 channels. Unused channel information is transmitted to the satellite at 0.1-sec. intervals and received by contracted vehicles 4 as movable bodies (10,000 units). Each of the movable bodies is supposed to transmit a signal to the satellite by ALOHA method and the signal is received by the ground station 2. Additional assumptions are as follows: (1) the membership accounts for 10% of all vehicles present nationwide of about 50 million

units, namely, five million units; (2) 20% of the five

million units, or one million units, are operated on roads;

(3) 200 bytes of information are gathered at every 10 min.

from each of the vehicles; (4) lines are 2 kbps x 10,000

lines (with a required bandwidth of 20 MHz according to the

QPSK modulation system); (5) the downlink is used for

broadcasting music, providing information for vehicles, and

other purposes; however, the basic application is to

transmit the same contents to all vehicles concerned and a

band of 10 MHz is divided into several bands for each of

different contents, and thus the downlink is excluded from

the simulation; (6) the uplink will be further deliberated.

Simulation is thus made on these assumptions and FIG. 6

shows a relationship among the number of calls made, call

loss probability, and line occupancy rate per 10 min.

The ALOHA method refers to a method of transmitting

information, in which a transmitting party transmits a

signal whenever it wants to and, if a collision is

encountered, the transmitting party retries. A method of

transmitting information thereof is not controlled. (A

form of Ethernet, in which retrial is attempted with a

certain time lag if a collision is encountered, is one type

of ALOHA method.)

A typical timing chart that represents a transmission/reception relationship between a movable body and a ground station based on the simulation described in FIG. 6 is shown in FIG. 7. Referring to the figure, a reference symbol "a" represents a condition, in which authorization to use a channel is yet to be established, taking 0.5 sec., a reference symbol "b" represents a condition, in which authorization to use a channel is established, taking 0.3 sec., and a reference symbol "c" represents a condition, in which a communication end is being waited + an unused channel delivery completion is being waited, taking 0.5 sec. A reference symbol "d" represents a simulation time slice of 0.1 sec.

The point of 10,000 on the horizontal axis in FIG. 6 corresponds to a case, in which each movable body makes an uplink once in 10 min. in this model. The theoretical maximum line occupancy rate shown in the figure can be obtained using (a + b)/(a + b + c + d), since the entire sequence time is a + b + c + d (a, b, c, and d taking the values cited earlier), of which data communication time is a + b. This represents a ratio of time during which uplink data is being received to a channel operating time where a connection is smoothly and ideally established with each

channel, that in this simulation being 57%. As the figure

tells, the call loss probability is about 20% when a call

is made once per 10 min. and, even if retrials to make up

for call loss are included, it is fairly easily possible

keep the call loss probability within 30%. It is expected

that a call collision probability will be relatively small

as the reduction ratio of the model approaches an actual

system. Even in an intended case of mega-access made by

one million users to 10,000 channels, therefore,

communications are possible without filling the uplink

bands. As is known from the foregoing discussion, the call

loss probability can be held to a level of about 20% and,

even considering bands for retrials, congestion can still

be avoided.

FIG. 8 shows status transition per channel on the

ground station side and FIG. 9 shows status transition per

one user on the movable body side.

FIG. 10 is a conceptual diagram showing an overall

information management system according to the invention

covering the entire areas of Japan. Uplink information 5

that is transmitted via a satellite 1 to the center

includes emergency information, such as accident and first

aid information, engine/brake failure and other failure

information, and predetermined interval information including a position, speed, direction, and condition (engine, electrical system, mechanical system) of the vehicle. Downlink information 6 transmitted from the center via the satellite 1 to each of the vehicles includes music information, image information, navigation information, road and traffic information, emergency information (callup), and new vehicle information. If the quasi-zenithal (for example: highly elliptic orbit)satellite system described in EP0880240A2 (hereinafter referred to simply as the highly elliptic orbit satellite) is used for the satellite, a comprehensive service network encompassing all areas of the nation can be achieved to provide services. A movable body overall information management system 13 serves as the core on the ground station side, provided with databases storing various types of data 14 and an analysis system 15. Through this analysis system 15, mandatory automobile inspection information and user information are distributed to an information requiring party 16, traffic information is distributed to another information requiring party 17, and safety information is distributed to a third information requiring party 18. The information requiring

party 16 includes, for example, a vehicle management

company, a maintenance and service company, and a vehicle

dealer. The information requiring party 17 may be a road

maintenance company, or a supervisory agency or

governmental organization. The information requiring party

18 is, for example, an insurance company.

FIG. 11 shows a movable body overall information

management system combined further with GPS. This

embodiment does not, however, preclude a case in which the

highly elliptic orbit satellite itself is provided with a

GPS function. A GPS signal is transmitted from a GPS

satellite 19 to each of movable bodies (ships and vehicles

in the figure.) 20. An automatic information exchange 22

is carried out between each of the movable bodies 20 and an

oblong satellite 1. These interactive communications are

relayed by way of the satellite 1, a transmission/reception

signal 23, antenna 3, a transmission/reception signal 24,

an information center 25, and a transmission/reception

signal 26 to an information user/service provider 27.

Information of various kinds as it relates to a movable

body 20 is automatically transmitted from the movable body

20 to the information center 25 which, based on the

information received, automatically gives an advice to the

service provider 27. Information is automatically
transmitted from the movable body to the center when the
movable body 20 becomes active, becomes stationary, and
when an emergency (accident) occurs therein (in which a
transmitter/receiver remains fully operational). This
basically takes place at random. Two signal transmission
and reception methods are available while the movable body
20 remains active (operating); namely, (1) the center 25
calls the movable body every 10 min., requesting
transmission of information, and the movable body 20
transmits information to the center 25 in response to it;
and (2) the movable body 20 transmits information to the
center 25 every 10 min. Whichever method that is
beneficial to line design is to be used.

FIGS. 12 and 13 describe typical operations in
interactive communications carried out using the system
shown in FIG. 11. The discussion assumes the following:
namely, the line specifications are 1 kHz (bandwidth), QPSK
(transmission method), and 2 kbps (transmission rate); the
maximum volume of data automatically transmitted and
received is 200 bytes/unit.session (= 1.6 kb/unit.session);
1 sec. is required for a single session (transmission of
200 bytes of data is completed in 0.8 sec. as calculated

from the line speed); the maximum permissible number of

sessions (line communications capacity per 1 min.) is 60

sessions/minute.line; and, the total number of lines is

10,000 and the theoretical number of sessions to be carried

out is 600,000 times/min. based on 10 MHz allocated for the

entire bands for sessions.

Immediately after the engine has been stopped 28,

the moving body 20 sends a transmission of information

without delay and, if an information reception acknowledge

signal is not received, it performs a transmission sequence

up to H times at G-min. intervals. For example, G = 1 and

H = 2. After the information reception acknowledge signal

has been received or a transmission has been sent F times,

the movable body becomes stationary 29. The key is then

inserted and a state is set immediately after engine has

been started 30. B min. after the engine has been started,

transmission is repeated at C-min. intervals until the

information reception acknowledge signal is received. For

example, B = 1 and C = 2. When the information reception

acknowledge signal is received, a state is set in which the

engine is operating 31. Information is then transmitted

after an information transmission request signal is

received; however, basically, information is transmitted

every D min. If the information reception acknowledge

signal is not received, transmission sequence is repeatedly

performed at E-min. intervals. For example, D = 10 and E =

1. When an accident occurs, a sensor is activated and an

emergency state 32 is established. In the emergency state

32, transmission is sent immediately and, if the

information reception acknowledge signal is not received,

transmission sequence is repeatedly performed at F-min.

intervals. For example, F = 1. When the information

reception acknowledge signal is received, a state is set

immediately after the engine has been stopped. A state

immediately after the engine has been stopped 28 is set if

the key is turned off in the state immediately after the

engine has been started 30, the state in which the engine

is operating 31, and the emergency state 32, respectively.

Between the information center 25 and the movable body 20,

there is carried out a transmission of the information

reception acknowledge signal in the state immediately after

the engine has been started 30, a transmission of the

information transmission request signal (polling) and the

information reception acknowledge signal in the state in

which the engine is operating 31, and a transmission of the

information reception acknowledge signal in the emergency

state 32. The information center 25 checks the received

information and performs automatic distribution to

information users/service providers. Analysis information

of various types is transmitted to the information

users/service providers 27, intended for a specific party

requiring the information and the received information is

checked and necessary actions are taken accordingly.

When a calling signal is received by the movable

body 20 in a ready state 33, calling signal reception

advice processing 34 is performed, which is followed by

requested information collection processing 35 and then

requested information transmission processing 36. In

requested information transmission processing 36, if a

requested information reception acknowledge signal is not

received, transmission sequence is repeatedly performed at

M-min. intervals, except that the sequence is executed only

after an automatic transmission, if one is being sent, has

been completed. For example, M = 1. The sequence is

terminated 37 when the requested information reception

acknowledge signal is received and then the movable body

returns to the ready state 33. On the side of the

information center 25, a calling signal reception advice

signal, as a result of the calling signal reception advice

processing 34 performed on the movable body 20 side, is

received in step 39. In this step 39, transmission is

repeated until the calling signal reception advice signal

is received before the operation proceeds to step 40 or 41.

In step 40, transmission is repeated at J-min. intervals

until retry count is I and at K-hour intervals after retry

count has exceeded I. For example, I = 10, J = 1, and K =

12. If there is no calling signal reception advice signal

in step 39, the operation proceeds to step 41, in which, if

no response is received after retry count has exceeded L,

retry sequence is interrupted and an alarm is issued. For

example, L = 70. In this step 41, contact with the

corresponding movable body 20 is disabled. If the

operation proceeds through step 40, it then proceeds to

step 38, in which a calling and requested information

transmission request signals are transmitted to step 33 on

the movable body 20 side. In step 38, the calling signal

and requested information transmission request signal are

transmitted to a specific movable body in response to a

request made by the information user/service provider.

Requested information is transmitted from step 36 on the

movable body side to step 42 on the information center 25

side, while a requested information reception acknowledge

signal is transmitted from step 42 to step 36. In step 42,
the information center is in a wait state for a maximum of
N min. until requested information is received. For
example, N = 1. The operation proceeds to step 43 after
the lapse of N min. and then to step 38. In step 43,
transmission is repeated at Q-min. intervals until retry
count is P and the retry sequence is interrupted and an
alarm is issued when the retry count exceeds P. For
example, P = 10 and Q = 1.

FIG. 14 shows the basic functions provided for a
transmission/reception terminal on the movable body side.
That is, an interactive communications function with the
information center via the oblong satellite 44, an
interactive communications function with the information
center via PHS 45, an interactive communications function
with the information center via a cellular phone 46, a man-
machine interface (I/O) function 47, and a movable body
information monitoring function 48 are, respectively,
interrelated with an information processing and
accumulation function 49.

Table 1 lists the types of transmission information.

Table 1

No.	Type of Information	Contents of Information	Use of Information	Typical Businesses Using the Information
1	ID No.	IP address	To specify the transmitting party	
2	Transmission time	Time-of-day and date of transmission		
3	Position when transmission is sent	Position information obtained through GPS	Tracking of a stolen car, probe car, identifying mutual positions among companion movable bodies, traveling route information	Expanding theft insurance business (reduced insurance premium rate → increased number of policyholders) Enhancing information service for automobiles (collecting more accurate traffic information and congestion information, enhancing navigation functions, etc.
4	Movable body equipment	Information on equipment and devices that are effective for quickly isolating faults and maintenance services (mileage, coolant temperature, coolant level, engine oil, brake oil, etc.)	Remote monitoring (predicting life expectancy and fault occurrence), quick maintenance service when a fault occurs [including remote maintenance (action advice)], identifying driving habits	Remote monitoring and maintenance business for movable bodies, expanding automobile company's maintenance business (enhanced service quality → gaining more customers), revising premium rate by insurance companies (differentiation from competitors)
5	Movable body operations	Information relating to operations and driving (driving speed, acceleration/ deceleration timing, engine speed, etc.)		

6	Accident	Sensor signal detecting the occurrence of an accident [seat belt/air bag activation information, acceleration sensor (impact detection sensor), etc.]	Passing accident information at early stages · To quickly take repairing actions for the damaged vehicle · To quickly rescue injured persons (calling an ambulance and the police at early stages)	Security businesses [police station, fire department (ambulance), hospital], automobile companies and maintenance companies, enhancing information service for automobiles (early prediction of expected traffic congestion), insurance companies

FIG. 15 is a conceptual diagram showing a typical system embodying the invention. Referring to the figure, vehicle condition information provided by a vehicle 51 may be classified into two groups, of which vehicle position information is transmitted to an artificial satellite 54 via an on-board device 52 mounted in the vehicle 51, on which various types of controlling devices are mounted, and an antenna 53. The vehicle position information may include longitude and latitude data provided by a navigation terminal. In terms of the scope of this invention, it is perfectly natural that the contract assumes distribution of music and/or image information and therefore the details in this regard will be omitted in the description of the embodiments to follow.

A signal reflected off the artificial satellite 54 (the satellite is preferably a non-geostationary satellite in an elliptic orbit, classified into a quasi-zenithal

satellite) is transmitted as vehicle information to a
centralized management center through, for example, an S-
band satellite communications and broadcasting system (as
an example of the quasi-zenithal satellite, a highly
elliptic orbit satellite system, which is hereinafter
referred to as HEO) 55.

Each vehicle is provided with various sensors that
detect vehicle operating conditions for providing vehicle
sensor information. Before the vehicle sensor information
is transmitted, it is possible to transmit and program in
advance vehicle body information used to determine a
specific vehicle model, including, for example, a vehicle
model, body serial number, date of manufacture, and the
name of a prefecture in which the vehicle is registered,
and user information. The vehicle is also provided with a
card reader/writer 57, with which a card for the exclusive
use by the user 58, for example, a credit card for payment
of toll charges, is to be used. This user card 58 is
recorded with user information which includes, for example,
the user name, date when the driver's license was obtained,
number of years of driving experience, and a bank account
number. The card can also be used for paying insurance
premiums of a vehicle insurance to be described later.

Vehicle body information and part of the vehicle sensor information are transmitted, as outline information, to the artificial satellite 54 via the on-board device 52 and the antenna 53. It is gathered at the centralized information center by the S-band satellite communications and broadcasting system 55 in the same manner as the vehicle position information.

The rest of the vehicle information is input and collected by, for example, a general-purpose DSRC (or dedicated short range communication) 58, through a dealer or directly to the centralized management center. The rest of the vehicle information includes user information, detailed information as part of vehicle sensor information, and vehicle body information. Data of gasoline purchased using the card 58 may be input and collected via a gas station in the same manner at the centralized information center 56 as electronic information. This provides fuel economy and engine information. Vehicle information of other types is input and collected at the centralized management center 56 through a radio communications means as a backup line 61.

The vehicle information collected at the centralized management center 56 is analyzed for use in statistical

analysis and diagnostics analysis. The vehicle information

used in statistical analysis and diagnostics analysis is

recorded in a computer database (DB) 69 and, at the same

time, provided for a nonlife insurance company 64,

committed automobile manufacturer and parts manufacturer 65,

used vehicle assessment company 66, governmental

office/municipal corporation 67, and a car rental

management company 68 through a network backbone, namely, a

public phone line and the Internet. It goes without saying

that these pieces of information are provided under

restricted conditions, such as through contracts, not given

with any limitations or principles. Providing vehicle

information from each vehicle also abides by certain

restrictions, such as contracts; it is not done with any

limitations or principles, either. A benefit of some sort

may be granted to a user who accepts to provide information.

FIG. 16 shows an on-board device. Referring to the

figure, the on-board device comprises a

transmitter/receiver device 71, a car navigation system 72,

a vehicle drive system 73, and an indicator/auxiliaries

system 74.

A signal from the antenna 53 is received through a

transmitter/receiver circuit 81 and a modulator/demodulator

circuit 82, demodulated by the modulator/demodulator circuit 82, decoded by a transmission/reception control circuit 83, and read in a CPU 85 through a bus 84.

The CPU 85 gets the transmission/reception control circuit 83 to encode the information to be transmitted, the modulator/demodulator circuit 82 to modulate it, and the transmission/reception control circuit 83 to send it through the antenna 53.

A card is read by a card reader/writer 57 and the data is read by the CPU 85 through a read/write control circuit 86. The data to be written in the card is, on the other hand, sent by the CPU 85 to the read/write control circuit 86 which, in turn, writes the data through the card reader/writer 57.

The user operates an I/O portion 88 to tell the CPU 85 what to do. The CPU 85 gives necessary information on a display device 89 of the I/O portion 88, or provides voice information through a means not shown.

The navigation system 72 is provided with a receiver portion 91, a display portion 92, a control portion 93, and an antenna 94. It has a record of a current position, route through which the vehicle has traveled, and map (road and traffic information) information, capable of providing

required information for the CPU 85 upon receiving a request made therefrom.

A portion enclosed by a rectangle representing the transmitter/receiver device 71, which comprises the antenna 53, transmitter/receiver circuit 81 and modulator/demodulator circuit 82, transmission/reception control circuit 83, CPU 85, I/O portion 88, card reader/writer 57, and the read/write control circuit 86, is the system used in the embodiment of the invention. It is further connected to other devices and systems to obtain required information.

These devices and systems are as follows.

The vehicle drive system 73 comprises an engine control device 95, automatic transmission device 96, brake control device 97 (anti-skid control), power steering device 98, and a drive system diagnostics system 99 for making a diagnosis of these devices every moment, each being connected to each other through an internal bus 100. The drive system diagnostics system 99 determines whether or not the value of an internal sensor in each of the devices falls within a specified range and a voltage and current fall within a specified range and stores the readings at predetermined intervals and whenever a faulty

value is detected. The stored data is read by the CPU 85

through a drive system interface 101.

The indicator/auxiliaries system 74 comprises a

light indicator control device 102 that controls headlamps

and turn signal lamps and indicates operations of a brake

and other vehicle devices, a power window control device

103, a height control device 104 that adjusts vehicle

height and vehicle dampers, a generator, an air conditioner

105, and other devices. Each of these devices is connected

to each other through an internal bus 106. An

indicator/auxiliaries system diagnostics system 107

diagnoses whether each of these devices is operating

normally and whether any is operated and retains fault and

operation data. The CPU 85 can read the retained data

through an indicator/auxiliaries system interface 108 as

necessary.

When a transmission of diagnosis results information

is sent from the diagnostics systems 100, 107, the CPU 85

determines whether it is necessary to transmit the

information to the artificial satellite and, when it

determines it is necessary to do that, directs the

transmission/reception control circuit 83 to transmit the

diagnosis results. The transmission/reception control

circuit 83 is provided with a channel with which a

permission to transmit is requested to the artificial

satellite which, in turn, allocates a transmission channel

for the transmission/reception control circuit. The

transmission/reception control circuit uses this channel to

send a transmission to the artificial satellite. Prior to

transmission of the diagnosis results, the CPU 85 can cause

the data to be input in the centralized management center

56 by giving the transmission/reception control circuit 83

the model of the vehicle, vehicle or user name, and other

data and transmitting the data to the artificial satellite.

It is also possible that the CPU 85 performs the same

function to input sensor information in the centralized

management center 56 upon receipt of a transmission of on-

board sensor information, without using the intervention of

the diagnostics systems 100, 107, thereby making a

diagnosis based on collected information. Vehicle

information can also be collected using this method.

FIG. 17 shows the system on the side of a

centralized management center that receives information

from vehicles. An antenna 111, transmitter/receiver

circuit 112, modulator/demodulator circuit 113,

transmission/reception control circuit 114, CPU 115, and an

I/O portion 116 have the same functions as those components

cited earlier. In addition to the CPU 115, there is

provided a task processing system 117 that is provided with

a computer or a processing device 118, retaining a large

volume of data. The processing device is connected via a

bus 168 to a server 119. The task processing system 117

organizes data according to the vehicle model, user, and

serial number and stores it in the server. It unloads data

from the server 119 to provide information as necessary.

FIG. 18 shows an outline of a satellite

communications and broadcasting system. Referring to the

figure, a reference numeral 150 represents a broadcast

station, a reference numeral 160 represents an artificial

satellite for broadcast (54 in FIG. 15), a reference

numeral 170 represents a GPS satellite, a reference numeral

180 represents a vehicle, a reference numeral 200

represents a car navigation system, and a reference numeral

190 represents an information display on the car navigation

system 200. The car navigation system 200 is provided with

a receiver device. It is also mounted in the vehicle 180,

serving as an on-board device for detecting positions,

searching for routes, and giving information display.

In addition, a reference numeral 240 represents a

satellite broadcast transmission signal from the broadcast
station 150, a reference numeral 155 represents a satellite
broadcast signal from the artificial satellite for
broadcast 160, a reference numeral 165 represents a signal
for position confirmation from the GPS satellite 170, a
reference numeral 220 represents an entire range of areas
subject to information transmission, a reference numeral
185 represents a traveling route through which the vehicle
180 moves, a reference numeral 210 represents an area
corresponding to the traveling route 185 of the vehicle 180
on the entire range of areas 220, a reference numeral 230
represents an area subject to information transmission on
the entire range of areas 220, and a reference numeral 185
represents an area in which the vehicle 180 is currently
present on the entire range of areas 220.

The entire range of areas subject to information
transmission 220 is broken down into small areas as shown
in FIG. 15. The broadcast station 150 and the car
navigation system 200 are to have the same information
concerning this division into small areas. The car
navigation system 200 is to be capable of identifying the
position of the vehicle 180, receiving the satellite
broadcast signal 155, and providing information.

The broadcast station 150 sets the area 230 for the area subject to information transmission and transmits information, with information identifying the area 230 appended thereto, by means of the satellite broadcast transmission signal 240 to the artificial satellite 160. The artificial satellite 160 for broadcast, which receives the satellite broadcast transmission signal 240, transfers it in the form of the satellite broadcast signal 155.

Having received the signal for position confirmation 165 from the GPS satellite 170, the car navigation system 200, on the other hand, has identified the position of the vehicle 180. The car navigation system 200 has also identified the area 175 in which the vehicle 180 is present on the entire range of areas 220. Moreover, the car navigation system 200 has identified the corresponding area 210 based on the retained data previously input by the driver or the traveling route 185 found through a route search function thereof.

Receiving broadcast, the car navigation system 200 receives the satellite broadcast signal 155 and reads information contained therein and one that identifies the area. At this time, it reads the information that identifies the area 230. The car navigation system 200 can

find the area 175 in which the vehicle 180 is present, the traveling route 185, and a point to which the vehicle moves.

The artificial satellite for broadcast 160 shall be one that is located in the zenith direction at all times when viewed from the ground and reception sensitivity of the car navigation system 200 may be focused on to receive signals only from the artificial satellite. This reduces radio disturbances caused by buildings and other structures, thus realizing a broadcasting system having no interruption of broadcast and providing information in accordance with the conditions of each movable body.

FIG. 19 is a flow chart showing collection, analysis, and processing method of vehicle condition information. Referring to the figure, (1) immediately after the driver or user has inserted the key and started the engine, a start signal is automatically transmitted from the vehicle to the centralized management center (S1). The HEO path, which is considered to have the lowest communications failure rate, is mainly used for the communications method, while the use of DSRC or cellular phones is to be permitted.

(2) Then, the center, having received the foregoing signal, transmits an acknowledge message for authorizing providing of information to the vehicle (S2).

- 54 -

(3) A confirmation is made with the driver whether or not to authorize providing of information (S3). A method of giving the confirmation is either voice or display. Response is to be given using two or more buttons on the on-board device.

(4) Only when it is authorized to provide information, individual vehicle information concerning each individual vehicle is collected and statistically analyzed (S4). Based on the data, vehicle information for a specific purpose, for example, classified according to insurance company, is collected and statistically analyzed (S5).

(5) Only when it is authorized to provide information, a system is started that adds up service points (S6). The service points is to be designed to increase in proportion to the mileage and the period of time through which the engine is running, providing a system whereby the more the vehicle is driven, the more the user is entitled to receive service benefits. Service points are to be managed according to not only the vehicle, but also the user. To accomplish this, an ID card issued for each individual user is to be inserted into the on-board device, which automatically transmits such

information as the age, sex, blood type, and other
information.

(6) The vehicle condition information, as the term
is used in the foregoing, refers to the following and the
level of disclosure may be selectable even when it is
authorized to provide information. <1> Vehicle position
information: longitude and latitude information obtained
through the navigation terminal; <2> vehicle control
information: brake operating amount, steering angle,
accelerator opening, gear ratio, ABS activation time, VSC
(skid control mechanism) activation time; <3> vehicle parts
condition information: oil temperature, oil pressure,
voltage, fuel level, CPU condition, muffler temperature.

(7) Data is encoded (S7) and transmitted to the
center (S8). Steps up to this point represent the
information collection function. Information processing
and analysis functions will next be described. (8) The
data is decoded at the center (S9), and (9) unprocessed
data for each vehicle model is stored in the database.

(10) Data is statistically analyzed for each model
(S10, S11). That is, <1> how frequent a new function
mounted to differentiate from competitors is used, and <2>
if utilization mode by model is unique, in terms, for

example, of time band, day of week, and application,

whether it is for commercial use or not.

(11) A performance analysis is made of each part

(S10, S12). That is, <1> if temperature is abnormal, <2>

if pressure is abnormal, and <3> if a product life is

appropriate. (12) The analyzed data is then stored in the

database (S13).

The data providing service for committed automobile

manufacturers and parts manufacturers will then be

described. This is concerned with a service to provide

committed automobile manufacturers and parts manufacturers

with the data stored through the information collection,

processing, and analysis functions described in the

foregoing flow chart. <1> Data is sold and provided

through a network in response to a request for purchasing

it made from a committed automobile manufacturer or parts

manufacturer (S14, S15). The network is a public switched

network and the applicable means can be selected according

to the customer needs. <2> Data is encoded before

transmission for fear of monitoring by other companies.

<3> The manufacturer which receives the data may be able to

use it in the following ways.

Applications of the statistical analysis data will

be described. <1> The statistical analysis information,
which tells a specific model used by a specific generation
in a specific time band on a specific day of the week, is
analyzed to deliberate on functions the model lacks in,
those overly provided, and pricing. <2> It is determined
how frequent a new function mounted to differentiate from
competitors is used and, if it is found that the function
is fairly frequently used, application to other models is
examined; if it is found that the function is not very
often used, then standard equipment and pricing are
reviewed and possibility is examined whether or not to even
abandon it. <3> A presentation is made to the dealer about
the fast-selling vehicle models and functions according to
age and sex, promoting sales effort classified by the
generation and sex of customers.

Applications of the performance analysis data by the
part will be described. <1> Identifying failure frequency
for each part will provide good evidence for attesting
validity of product life. <2> When advice of an abnormal
condition is received from a user (driver), unprocessed
information before and after the failure and performance
analysis data are provided in a package for the repair
company and dealer, thereby helping them identify a cause

or causes of the abnormal condition that is not reproduced easily.

The data providing service for used car-related businesses will be explained. This is concerned with a service to provide used car sales agents and dealers with the data stored through the information collection, processing, and analysis functions of system example 1 (S18). <1> A vehicle purchaser connects to the center in an effort to find the assessed value of his/her own car. <2> The center examines in details information used to determine internal conditions of various pieces of vehicle equipment (e.g., engine control information, steering wheel angular velocity, ABS cumulative activation time, and VSC cumulative activation time) and information on driving routes harmful to the vehicle (seashore, snow-covered roads: both contributing to salt damage), in addition to the inspection record of the vehicle for which an assessment is requested, mileage, and model and type, thereby calculating and determining an assessment value. <3> The foregoing method allows the service to be provided also for dealers, used car sales agents, wreckers, and automobile repair shops in which trade-in vehicles are likely to be driven in.

The data providing service for the Environment
Agency will be described. This is concerned with a service
to provide the Environment Agency with environment-related
information of all the data stored through the information
collection, processing, and analysis functions described in
the foregoing flow chart. <1> Hazardous gases contained in
the exhaust emissions from the engine are sampled at random
and checked to see if the environmental standard values are
met. <2> A statistical analysis is made for each vehicle
model and, if the predetermined number of vehicles fall
short of the standard value in a specific model, the
Environment Agency makes an improvement recommendation for
the model.

The data providing service for car rental companies
and rental car users will be described. This is concerned
with a service to provide car rental companies with
position information of all the data stored through the
information collection, processing, and analysis functions
described in the foregoing flowchart.

For car rental companies: <1> When a rental validity
expires of a rental car or a car used for community
transport, the car automatically transmits its position
data to the center via HEO. <2> The center sends a

transmission to the rental car management company to enable the management company to start monitoring the rental car whose validity has been expired. Possible methods of providing the information are a) longitude and latitude information; b) place name information; and, c) map showing graphic screen information. "Community transport" as the term is used in the above context means an urban rental car system that allows a number of rental cars to be shared among a specific community and any to be left unattended after use.

For rental car users: <1> Though corresponding to a different category under the current division, this service transmits commercial information applicable to a specific area to users. <2> A commercial provider is tied up with a car rental company and, if a user accepts to receive commercial information, part of the rental fees will be returned in cash. <3> Possible media are the navigation monitor and only through audio.

The data providing service for municipal corporation electronic road pricing will be described. This is concerned with a service to provide a municipal corporation with information as it relates to a predetermined restricted zone (e.g., municipal boundary), whether the

vehicle has moved therethrough, time of entry therein, and a cumulative time of driving therethrough, of all the data stored through the information collection, processing, and analysis functions described in the foregoing flowchart. <1> To a vehicle approaching the restricted zone, an automatic transmission is sent from the center via HEO (oblong satellite; the same abbreviation is hereinafter used) and the HEO informs the vehicle that "you are approaching the restricted zone" and that "you will be charged for a sum per a predetermined period of time if you drive through it." Available methods to determine that a vehicle enters the restricted zone are by means of position information as found through the on-board GPS function and through a DSRC on the road side without using HEO. <2> After the advice given in step <1>, the on-board device is used to constantly monitor whether the vehicle has moved past the restricted zone and, when the vehicle does move past the restricted zone, information on the entry time, days or date of use of the restricted zone, and cumulative time through which the restricted zone is driven is transmitted via HEO to the center. <3> Settlement methods are post batch billing, on-the-spot payment by ETC, and prepayment.

The data providing service for nonlife insurance

companies will be described. This is concerned with a

service to provide nonlife insurance companies with

information for calculating premium rates and share of

liability in accidents of all the data stored through the

information collection, processing, and analysis functions

described in the foregoing flow chart (S14). <1> A service

can be provided, in which insurance premiums are paid only

for the time band through which the vehicle is used.

Possible payment methods for the on-demand insurance

(designed for those drivers who do not drive vehicles often,

for weekend drivers; low-premium insurance without having

to make an annual contract) include deferred payment for a

predetermined period of time (e.g., one month), on-the-spot

payment by ETC card, and settlement by card at the end of

driving, in addition to the conventional advance payment.

<2> Insurance premiums are calculated by classifying the

route, discriminating between a frequently driven road and

a completely new one, and between whether the vehicle moves

through an accident-ridden spot and one with almost no

accident. To ensure right to privacy, information on

longitude and latitude is not necessarily provided and,

instead, the on-board device may be used to determine the

foregoing discrimination and a corresponding code is transmitted. For instance, a road which has not been driven for the past one year is 0, a road otherwise classified is 1, and the vehicle's traveling past an accident-ridden spot is 2; and, it is not necessary to provide information on when and where the vehicle has traveled.

The vehicle information providing service for nonlife insurance companies will be described in detail with reference to the flowchart shown in FIG. 20. Like the foregoing examples, a music/image distribution contract has been concluded with the controlled vehicle in question.

<1> Immediately after the driver or user has inserted the key and started the engine, a start signal is automatically transmitted from the vehicle to the centralized management center (S21). This starts collecting (1) vehicle position information, (2) vehicle control information, and (3) vehicle parts condition information according to the flow shown in FIG. 16. In the meantime, the applicable vehicle model, user name, and other types of attached information in addition to the foregoing information are separately collected and analyzed at the centralized management center as described earlier.

<2> Fees are calculated at the center according to the vehicle model and user name and fee advice and a confirmation message are transmitted to the vehicle (S22). The user of the vehicle is prompted to determine whether he or she wants to use the insurance (S23). In this example, the user's intention to use the insurance or not is inquired through the vehicle, thereby concluding the contract on the spot; however, needless to say it is possible to conclude the contract in advance, in which case, validity for a predetermined period of time can be set up for the contract. In addition, the validity may be on a short term as in this example and it could be a specific date only or the number of days according to an itinerary. In this example, the validity is considered to be a predetermined period of time, as it is stipulated in the contract.

<3> When the user's intention to use the insurance is transmitted, vehicle utilization time data and via point data, which are added up at predetermined intervals, are encoded and transmitted by the on-board device (S24). Measurement of data can be taken continuously instead of at predetermined intervals. In this case, recording through data collection may be limited only to unique events. In

the example, driving time data is obtained and used for

calculating the charging time. Depending on the specific

details of the contract, the charging time may be all or

part of the total driving time. In addition, via point

data of known, unknown, and accident-ridden spots through

which the vehicle moves are also collected. These spots

may be registered by the central management system at the

center or confirmed that they are yet to be registered. It

is further possible to make other driving or vehicle

information available in electronic form. It may for

example be possible to collect frequency data of sudden

braking, abrupt steering, and sudden starts and total

acceleration value data of each of these items. Instead of

a spot, an area including that spot may be used. The

description hereunder is concerned with spots. These

pieces of data are decoded at the center (S25) and stored

as unprocessed data for each user (S26). That is,

unprocessed data are stored for nonlife insurance companies,

fee calculation outsourcing service companies, and users.

<4> The collected data is used for sale of

unprocessed data to nonlife insurance companies (S27) and

provided for fee calculation outsourcing service companies

(S28). In the meantime, service record information in the

form of data is separately provided for the fee calculation

outsourcing service companies so that it is incorporated in

calculation of insurance premiums (S29). Such information

as the past periodic inspection and service records is

collected, including, for example, the number of days

elapsed since the last service maintenance job. The

information is collected by letting the vehicle send a

transmission if it is provided with a memory, or by letting

the vehicle maintenance service companies send it over the

network.

<5> The fee calculation outsourcing service company

calculates the charging time based on the driving time data,

validates it, and makes a calculation for settlement by

coupon tickets and a calculation for deferred payment. It

also makes a calculation of insurance premiums according to

via point data by setting a low premium rate for known

spots, a high premium rate for unknown spots, and a high

premium rate for accident-ridden spots. This setting is

referred to, in this specification, as weighting of

insurance premiums. It goes without saying that, instead

of a premium rate for basic insurance premiums, the

insurance premiums themselves may be calculated.

For a contracted vehicle, driving time for a

predetermined period of time is collected and via point

data representing points through which the contracted

vehicle has been driven (including traveled routes and

areas as described earlier) is collected; charging time

data is established based on the driving time data and a

weighting of insurance premiums is established based on the

charging time data or via point data, or both, thereby

calculating and displaying the amount charged as insurance

premiums based on the charging time data, via point data,

and insurance premium weighting. It is of course possible

to calculate points acquired from the driving time data and

the number of specific points driven through, based on

which the amount charged as insurance premiums is

calculated. Even with this approach, a time to be charged

is set for calculation and a points count is set using via

point data, which serves as adopting weighting for

insurance premiums. For the purpose of the weighting of

insurance premiums, one or a combination of the following

types of information may be used: vehicle control

information, vehicle parts condition information, vehicle

(e.g., whether it is new or old) and user information, and

maintenance and historical information.

<6> Charging to users is processed according to the

amount charged as insurance premiums (S32). For example, the sum is debited from the user's account through the aforementioned card according to a deferred payment system. This charging to users includes charging of insurance premiums for PL (product liability) for the vehicle or parts manufacturers and charging of insurance premiums based on an analysis made of the share of liability in accidents.

Thanks to a statistical analysis of vehicle condition information made possible through the positive and proper information collection system, it is possible to review and revise the amount of insurance premiums at the time of contract renewal, as changed from the existing advance payment method.

When the invention is embodied in vehicle insurance, it is possible to statistically identify the frequency and condition of utilization of vehicles on a real-time basis, which makes possible charging of insurance premiums in accordance with the frequency and condition of utilization of vehicles. This diversifies the form of insurance contract, without being limited to payment of premiums on an annual contract. For example, it permits deferred payment of insurance premiums.

More specifically, outlined condition information of
vehicles that run throughout Japan is centrally managed at
the center using HEO and, through an additional and tie-up
use of DSRC, IMT-2000, or other broadband mobile
communications system, detailed condition information is
also gathered. Then, mining of this data is carried out
and a service is rendered to provide charged information.

FIG. 21 shows a flow of information services and
contract fees in a basic business of "music/broadcast +
interactive communication."

In compliance with a contract concluded among a
movable body user 400 owning a vehicle 4, a broadcasting
music company (a company distributing broadcasts and music)
300, and a movable body overall information management
system management company 13, music and/or image are
broadcast for the movable body overall information
management system 13 and a music/image broadcast service is
provided from the movable body overall information
management system management company 13 to the movable body
user 400. In payment for the service, the movable body
user 400 pays a music/broadcast subscription fee to the
movable body overall information management system 13 which,
in turn, pays a music/broadcast fee to the broadcasting

music company 300. In this invention, the management

company may collect the subscription fees from a large

number of users and pays the broadcasting music company the

total sum all together.

Various methods are possible for payment of fees

which may be entrusted with a finance company or made into

bank accounts. According to the invention, the movable

body user receives music and image as the basic service,

for which the user pays a subscription fee. In the

meantime, the invention allows the same device as the

receiver (that is, the receiver is to be used as a

transmitter/receiver) to transmit information at

predetermined intervals, of which the movable body user may

or may not be aware. The management system is therefore

allowed to analyze the transmitted information, thus adding

value to it to create a new form of service for a greater

convenience to the movable body user and, at the same time,

added room for an increase in the subscription fee.

The management company collects subscription fees

from movable body users and pays the total sum all together

as a content providing fee to the broadcasting music

company. The management company therefore assumes risks of

collecting subscription fees and finding subscribers to pay

the broadcasting music company a predetermined amount of broadcast/music content providing fees. The basic function of the broadcasting music company is to provide content and therefore the broadcasting music company means a broadcast and music content provider. The overall management company owns a satellite to establish an uplink (according to the preferred embodiment of the invention, though there may be another company involved through which the uplink is established). To sum up, it is the aim of the invention to enhance convenience of the service by having a single terminal both for receiving broadcast and music and sending transmission. A mutual information exchange contract is also concluded between an insurance company and a system company. That is, a user is entitled to a reduction in insurance premiums if he or she is found to seldom apply sudden brake as judged from daily driving habits. Information is transmitted automatically without the driver's knowing it as he or she listens to a broadcast or music during driving and information collected from a large number of drivers is then analyzed.

Based on the broadcast contract described in the foregoing being concluded, a vehicle management company 16 (maintenance company, dealer, automobile manufacturer,

etc.) provides the user 400 with new vehicle information

and customer-by-customer advertisements by way of the

movable body overall information management system 13. The

user 400 provides the movable body overall information

management system management company 13 with movable body

equipment operating information, position and time-of-day

information, and emergency/accident occurrence information.

From the management company 13, the movable body equipment

operating information is transmitted as movable body

equipment/operation analysis information and the position

and time-of-day information is transmitted as congestion

analysis information and emergency/accident occurrence

information to the vehicle management company 16. From the

vehicle management company 16, emergency action information

is provided for the corresponding user by way of the

overall information management system management company 13

and, from the overall information management system

management company, emergency action information is

provided for the movable body user 400. A mutual

information exchange contract is concluded between the

overall information management system 13 and the vehicle

management company 16.

There is also concluded a mutual information

exchange contract between a road maintenance company 17 (including a supervisory agency, governmental organization, and police) and the movable body overall information management system management company 13. Traffic information and navigation information are provided from the road maintenance company 17 to the system management company 13, while congestion analysis information and emergency/accident occurrence information are provided from the system management company 13 to the road maintenance company 17. Moreover, emergency action information is provided from the insurance company 18 to the system management company 13, while emergency/accident occurrence information and movable body equipment/operation information are provided from the system management company 13 to the insurance company 18. The system management company 13 pays the insurance company 18 emergency action fees and insurance premiums.

The traffic information and navigation information provided by the road maintenance company 17 are distributed to the movable body user 400 by the system management company 13. This service is based on, as a prerequisite, a mutual information exchange contract previously concluded between the user 400 and the system management company 13

and the user 400 is to pay the system management company 13

traffic information fees, and the insurance company 18 via

the system management company 13 emergency action fees and

insurance premiums. A method is also available, in which

the emergency action fees and insurance premiums are paid

directly to the insurance company and it is also the scope

of this invention that commission is added when the payment

is made through the system management company. Furthermore,

it is allowed that various types of information are used in

emergencies within the movable body overall information

management system management company 13 and a national

government and municipal government 500.

As apparent from the foregoing description, since a

vehicle, which is driven by a driver who has concluded a

contract to subscribe to sound or image information by

means of interactive communications via a satellite, is

provided with the probe car function according to the

invention, traffic control can be provided smoothly and

public actions of various kinds and insurance actions can

be taken by deriving information from vehicle owners. The

invention also provides convenience, with which the movable

body user is provided with appropriate services in return

for information provided by the user even without his or

her knowing it.

While a preferred embodiment of the invention has been described using specific terms, such description if for illustrative purposes only, and it is to be understood that changes and variations may be made without departing from the spirit or scope of the following claims.